


<b>Model No.</b> <b>CK2003</b>	<b>High Tenacity Polyester PVC Laminated Fabrics</b>
<b>General Applications:</b>	Construction, Marine (Field) covers, Storage covers and many other applications
<b>Colors:</b>	White, Green
<b>Type of Products:</b>	Roll Type - 2M x 45M
<b>Flammability Test Method:</b>	EN 71-2: 2011 +A1:2014 - Flammability



抗水  
Water  
Resistant



不變形  
Dimensional  
Stability



阻燃  
Flame  
Retardant



長壽命  
Long  
Lasting




抗紫外線  
UV  
Resistant



色牢度  
Color  
Fastness

### Physical Properties:



Fabric Detail 網布規格	200D x 300D			
Item 項目名稱	Test Method 執行標準	Unit 單位	Value 數據	
Thickness 厚度	DIN53353	mm	0.3	
Total Weight 總重量	DIN53352	g/m <sup>2</sup>	301.7	
Tensile Strength 拉伸強度	DIN53354	N/5cm	經 Warp	526.5
			緯 Weft	361.5
Elongation at Break 斷裂伸長率	DIN53354	%	經 Warp	16.5
			緯 Weft	141.5
Tear Strength 撕裂強度	DIN53363	N	經 Warp	147.7
			緯 Weft	125.0
Adhesion of Coating Strength 剝離負荷	DIN53357	N/3cm	經 Warp	N/A
			緯 Weft	0.79 kg/cm
Remarks 備註				

This technical data is offered as helpful suggestion only.  
It's accurate to the best of our knowledge at time of  
printing.