



Head protection

LIPARI2 T5

SAFETY GLASSES

Extra flexible, shade 5 safety glasses with side protection for light welding work



Specific benefits



Comfort

· Temple length and ratchet angle adjustments for a perfect fit



Easy to use

· Anti-slip ends for an increased comfort and very good hold on the head (or on a helmet)



Compatibility

· Flexible nose pads for an optimised comfort and a perfect fit for all body types



Cost-effective

· Fashionable frameless design with high impact protection at an economical price



Benefits elements

· Ear protection compatibility

Applications

- Public works
- Finishing works / Craftsmanship
- Education
- Heavy industry
- Maintenance

Certifications and norms



EN169

UV 5

EN166

1 FT / FT

ANSI Z87.1 - IMPACT

Z87+ L5

Protects against risks



Shock



UV / IR



Head protection

LIPARI2 T5

SAFETY GLASSES

Extra flexible, shade 5 safety glasses with side protection for light welding work

Standards - Details

Technical details

Use	Inside/outside
Type of eye protection	Glasses
Lens matériel	Polycarbonate
Lens treatment	Anti-fogging (classic), Anti-scratch (classic), UV400
Lens support	Monobloc
Lens color	Welding 5
Optical class	1
Lens protection class	5
Lens characteristic	Curved
Mechanical strength (lens)	F, T
Nose pad material	TPE (Thermoplastic elastomer)
Frame material	Nylon
Frame	Temples
Frame color	Yellow, Grey
Mechanical strength (frame)	F, T
Temples benefit	Adjustable width and height, Non-slip temples, Flexible tip
Temples confort	Non-slip temples, Flexible tip
Weight (g)	34








Head protection

LIPARI2 T5

SAFETY GLASSES

Extra flexible, shade 5 safety glasses with side protection for light welding work

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LIPA2T5	Shade 5	-	LIPARI2 T5	3295249156701	13295249156708	100	10	6.3 kg	31.0 cm	56.4 cm	40.4 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height