



- 1 to 4 gas monitoring for O₂, H₂S, CO & combustible gases
- 18-hour runtime with lithium-ion battery
- Includes vibrating, 90 dB audible, and LED visual alarms
- Two-year, all inclusive warranty

Industrial Scientific is pleased to offer the M40, a versatile multi-gas monitor capable of detecting CO, H₂S, O₂, and combustible gases for a wide variety of hazardous and confined space applications.

The M40 is housed in a rugged, impact-resistant case to provide superior performance and durability in harsh environments and resistance to radio-frequency and electromagnetic interference. Its four-button interface provides simple, intuitive operation and calibration, and the M40's five-second "Off" feature prevents unintentional shut-offs. The unit's compact size and economical price make it an ideal personal monitoring instrument.

Other standard features include a vibrating alarm, lithium-ion battery, peak/hold readings, large LCD, 75 hour datalogging capacity, and belt clip. An optional compact parasitic sampling pump enables remote sampling from up to 50 feet away. The M40 carries a two-year warranty.

SPECIFICATION

Case:

High-visibility, impact resistant composite – RFI, EMI and ingress protection tested and approved

Dimensions:

10.9 cm x 6.22 cm x 3.48 cm (4.30" h x 2.45" w x 1.37" d)

Weight:

244 g (8.6 ounces)

Weight with pump: 326 g (11.6 ounces)

Sensors:

Combustible Gases – Catalytic Diffusion

Oxygen and Toxic Gases – Electrochemical

Measuring Ranges:

Combustibles – 0 to 100% LEL in 1% increments

Methane – 0 to 5% of volume in 0.1% increments (M40-M only)

Oxygen – 0 to 30% of volume in 0.1% increments

Carbon Monoxide – 0 to 999 ppm in 1 ppm increments

Hydrogen Sulfide – 0 to 500 ppm in 1 ppm increments

The M40 features LEL over-range protection

Power Source:

Rechargeable lithium-ion integral battery

Runtime:

18 hour – instrument (non-alarm)

12 hour – instrument with pump (non-alarm)

Display:

Large LCD provides simultaneous and continuous readout of up to all four gases. Large, high-contrast characters, graphic icons and unique amber backlight provide clear display visibility in low-light conditions.

Alarms:

Vibrating, 90 dB audible and ultra-bright LED visual alarms. High/low, STEL, TWA and low battery alarms. Flow alarm indicator when used with optional SP40 pump.

Datalogging:

Up to 75 hours of datalogging capability

Temperature Range:

-20° to 50°C (-4° to 122°F)

Humidity Range:

15 to 95% RH, typical, 0 to 99% RH intermittent (non-condensing)

IP Rating:

IP64

Approvals:

UL – Class I, Groups A,B,C,D T4; Class I, Zone 1, AEx ia d IIC T4

CSA – Class I, Groups A,B,C,D T4

MSHA (M40-M only) – Intrinsically safe for Methane/Air mixtures only

ATEX – EEx ia d IIC T4

Equipment Group and Category II 2G

Australia – Ex ia s Zone 0 IIC T4

Russia – GOST R

INMETRO – BR - Ex ia d IIC T4